Hyosung MX7800T

Multi-function Through the Wall Walk Up

Hyosung branch transformation solutions have been designed to deliver seamless migration of transactions from the teller line to self-service. The **MX7800T** is a multi-function ATM with more features and functionalities than a standard ATM. The **MX7800T** gives consumers the ability to perform more complex transactions with the help of on demand video assistance. At Hyosung, every ATM product, service, and support system is engineered to be reliable and flexible. Complementing the extensive range of offers Hyosung delivers inside the branch, the **MX7800T** extends the reach of transformative solutions through the wall.





KEY FEATURES

ULTIMATE FUNCTIONALITY

• The 7800T offers ultimate functionality, featuring bill payment, denomination selection, funds transfer and mobile top-up in a highly userfriendly interface for maximum convenience and ease of transition

MAXIMUM RELIABILITY

- The 7800T is designed to provide reliability that is second to none in the market, with the highest uptime and with minimum maintenance needs
- The 7800T is designed to run problem-free and typically has 99% availability

CONVIENCE

The 7800 takes up to 50 transactions in one transaction

FLEXIBILITY

- The 7800 series comes ready with Active Teller that allows a teller to assist customers remotely via video
- The 7800T allows branch employees to serve more customers in new ways by eliminating manual processes. In addition, it allows branch staff to focus on identifying and promoting bank products that can help customers attain their financial goals

SECURITY

- Hyosung ATMs support both physical and logical defenses against a variety of attacks. Multi-level antiskimming, locked down operating system, white-listing, and encryption combine for a formidable defense
- The 7800T easily integrates with any monitoring solution to provide seamless data transfer for effective management of self-service channels

SPECIFICATIONS

DIMENSIONS

- Height: 63.5"
- Width: 30.8"
- Depth: 35"
- Weight: 2,030 lbs.

ENVIRONMENTAL

- Temperature: 32°F 104°F (0°C~ 40°C)
- Humidity 25% 85%

SOFTWARE

- Microsoft® Windows® 7
- Professional/Windows 10 ready

CUSTOMER INTERFACE

- 19" Landscape Display TFT LCD (1024 X 768)
- Input Method IR Touch Screen
- Privacy Filter –19" Filter
- Guide Light Flicker, BCR Option
- PIN Pad PCI 3.0 EPP
- Audio Guidance– sound card
 on board
- ADA Audio Guidance Available with earphone jack, voice I/F 3
- Card Reader DIP Reader EMV compliant, anti-skimming and anti-shimming
- Reader (via card, smartphone or smartwatch)

MEDIA TECHNOLOGY

- Dispense
 - Configurable denominations (5 cassettes)
 - Maximum dispense 50 notes for 1 transaction
 - 3,000 notes per cassette
- Cash & Check In Module
 - Mixed media depository
 - 75 item insertion (mixed)
 - Capacity: 3,000 items per cassette
 - 4-way deposit direction

SECURITY

- Safes: CEN1
- Alarm Seismic + Heat
- Locking Device Cencon Shunted
- Key Lock Common Key
 Security Terminal Block
- Security Terminal Block (External I/F)
- CCD Camera I/F Video Port with pig tail for internal cam, video power with pig tail for cam

SERVICING

- Rear access
- State of health indicators across all modules
- 15" TFT LCD Supervisor panel, Input: Res touch screen

PRINTER

- Thermal Line Printing Thermal roll paper
- 3.1" graphical thermal receipt printer

MAIN CONTROLLER

- CPU I5-4590 3.3 GHz (Q87)
- Expansion Slots PCI 2EA, PCI Express 1X 1EA, PCI Express 16x 1EA
- Serial Ports 6 port
- USB Ports 13 Ports (USB 3.0 : 4, USB 2.0 : 9) + 7 port USB 2.0 Hub
- VGA GT520 VGA Card (OPL: DVI, SPL : VGA) On-Board VGA
- LAN 10/100/1000 Mbps On-Board

ADDITIONAL INFORMATION

- Communication TCP/IP
- Electronic Journal
- System Battery
- NFC 13.56MHz ISO14443 Type A,B NFC and Mfare
- Power Supply: AC 110-240V, 50-60 Hz, Back-up battery (reserving last transaction & safe shutdown)

OPTIONAL

- Card Reader Motorized EMV Compliant, anti-skimming and anti-shimming included
- ID Scanner
- Web Camera
- Mic
- Palm Vein Scanner

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.