

HYOSUNG

5L

A robust, secure, and high-capacity solution.

The **5L** allows complete deployment flexibility and a broad range of non-traditional offerings. The **5L** is ideal for in-branch or off-premise deployments, and offers the best in class solution when high availability, security, and high capacity are required.

Features

Highest Availability

The **5L** is designed to provide exceptional reliability, unequaled in the market with minimum maintenance and maximum uptime.

Flexibility

Designed with an open architecture platform, the **5L** allows for easy future upgrades and module modifications. The modular design and compact footprint are designed to save our customers cost and provide maximum convenience. A full range of advertising and marketing support is available with the **5L**.

Capacity

The **5L** has high capacity, high cash dispense capability, and the ability to support large volume transactions.

Security Options

Hyosung ATMs defend against physical and logical with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The **5L** is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Specifications

Dimensions

- Height: 58.3 inch (1418 mm)
- Width: 18.9 inch (480 mm)
- Depth: 33.3 inch (845 mm)
- Weight: 1095.7 lbs (497 kg)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
With Heater: 14°F – 104°F (-10°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10
- Hyosung MoniPlus™ including Hyosung MoniGuard™ Security
- Hyosung MoniCRM™
- Hyosung Connect
- Hyosung MoniManager™

Customer Interface

- 19" LCD touch screen (15" optional)
- Privacy filter
- PCI complaint EPP
- Headphone jack with Volume Control
- Card Reader – DIP, EMV compliant
- Contactless – Integrated reader (via card, smartphone or smartwatch)

Media Handling

- **Cash Dispenser**
 - Configurable denominations up to 5 high capacity dispense cassettes
 - 3,000 notes* per cassette
 - Bundle present, bundle retract
 - Note by note rejection
 - Automatic shutter

Security

- UL291 level 1 Safe
- Seismic & Heat detector
- Locking Device: Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- IP or Analog security camera (optional)
- Awareness Mirror
- Hyosung MoniGuard™ Solutions
- Trusted Platform Module (TPM)

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Front Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%,
200V ~ 240V±10% 50/60Hz

Additional Features

- Backup battery reserves the last transaction & safe shutdown
- Barcode reader (optional)
- Fingerprint reader (optional)
- Heater (optional)

*Subject to media quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.