

Hyosung is a world leading convenience deployment brand. The **MX5600** allows complete deployment flexibility and a broad range of non-traditional offerings. The **MX5600** is ideal for in-branch or off-premise deployments, and offers the best in class solution when high availability, security, and high capacity are required.

KEY FEATURES

HIGHEST AVAILABILITY

The **MX5600** is designed to provide exceptional reliability, unequaled in the market with minimum maintenance and maximum uptime.

FLEXIBILITY

Designed with an open architecture platform, the **MX5600** allows for easy future upgrades and module modifications. The modular design and compact footprint are designed to save our customers' cost and provide maximum convenience. A full range of advertising and marketing support is available with the **MX5600**.

CAPACITY

The **MX5600** has high capacity, high cash dispense capability and the ability to support large volume transactions.

SECURITY OPTIONS

Hyosung ATMs defend against physical and logical with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The **MX5600** is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



SPECIFICATIONS

DIMENSIONS

- Height: 59.3"
- Width: 18.2"
- Depth: 31.9"
- Weight: 978 lbs

ENVIRONMENTAL

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- With Heater: -24°F – 104°F
- Humidity: 25% – 85%

SOFTWARE

- Microsoft Windows® 10

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method – Touch screen
- Privacy Filter – 15" filter
- PIN Pad – PCI compliant
- ADA audio guidance – earphone jack
- Card Reader - DIP, EMV compliant
- Contactless – Integrated reader (via card, smartphone or smartwatch)

MEDIA TECHNOLOGY

- Dispense
 - 3,000 notes per cassette
 - Configurable denominations
 - Up to 5 high capacity dispense cassette
 - Bundle present/retract
 - Note by note rejection
 - Automatic Shutter

SECURITY

- Safe – UL 291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic safe lock, KABA Mas Cencon (optional)
- Sensor – Safety door sensor
- Security – Terminal block for easy security connections
- Key Lock – Common Key
- Security camera

SERVICING

- Front access
- State of health indicators across all modules

PRINTER

- 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication – TCP/IP

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.