

Hyosung is a world leading convenience deployment brand. The **MX5600T** allows complete deployment flexibility and a broad range of non-traditional offerings. Ideal for in-branch or off premise deployments, the **MX5600T** offers the best in class solution when high availability, security, and high capacity are required.

KEY FEATURES

HIGHEST AVAILABILITY

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime. The **MX5600T** is designed to provide reliability that is unequalled in the market, with minimum maintenance and maximum uptime.

HIGH CAPACITY

The **MX5600T** has high capacity, cash dispense capability and the ability to support large volume transactions.

FLEXIBILITY

Designed with an open architecture platform, the **MX5600T** allows for easy future upgrades and module modifications. The **MX5600T** features a small footprint and compact design.

FUNCTIONALITY

The **MX5600T's** expanded functionality includes bill payment and funds transfer, in a highly user-friendly interface, for maximum convenience.

SECURITY OPTIONS

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, white-listing, encryption, and anti-skimming.



SPECIFICATIONS

DIMENSIONS

- Height: 61.1"
- Width: 18.2"
- Depth: 43.7"
- Weight: 1023 lbs

ENVIRONMENTAL

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- With Heater: -24°F – 104°F
- Humidity 25% – 85%

SOFTWARE

- Microsoft Windows® 10

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method – IR touch screen
- Privacy Filter
- PIN Pad – PCI compliant
- ADA Audio Guidance – earphone jack
- Card Reader - DIP, EMV compliant
- Contactless - Integrated reader (via card, smartphone, or smartwatch)

MEDIA TECHNOLOGY

- Dispense
 - Configurable denominations up to 4 cassettes
 - 3,000 notes per cassette
 - Bundle present/retract

SECURITY

- Safes – UL 291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic Safe Lock, KABA Mas Cencon (optional)
- Security camera

SERVICING

- Rear access
- State of health indicators across all modules

PRINTER

- 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication – TCP/IP
- Heater Optional
- Privacy filter

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.